

Deployment Configuration

Managed documentation for Deployment Configuration.

- [Environment Variables](#)
- [systemd Services](#)
- [Nginx Configuration](#)
- [Ports and Network Bindings](#)

Environment Variables

Environment Variables

Field	Value
Distribution	WCT English — OpenC5ISR
Product	OpenC5ISR
Release	0.15.1
Deployment	openc5isr-en.wallacecorptech.com
Source	/srv/wct/releases/OpenC5ISR-v0.15.0
Evidence	Static environment-reference scan; values redacted
Source fingerprint	63d2b1097707e25d666401cdc6362e395968600a40a08690210cd8c0b75fbf50
Status	Generated baseline — human review required

“ **Verification boundary:** This page combines platform design guidance with static evidence from the release. It does not prove that every detected interface is enabled, reachable, secure, or operational in the deployed environment.

Observed variables

Variable	Secret-like	Observed default	Mechanism	Evidence
ADDRESS	No	—	interpolation	openrf/agent/functions/probe-n310.sh
AEGIS_SENTINEL_LABEL	No	COMPILED_DEPLOYMENT.aegisSentinelLabel).trim() COMPILED_DEPLOYMENT.aegisSentinelLabel	process.env	server.js tools/integrate_opensof_service_entries.py
ALT	No	—	shell	edge/openssa-sensor/install-demo-sensor.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
ANTHROPIC_API_KEY	Yes	—	process.env	server.js lib/openllm/agents.js lib/openllm/providers.js
API	No	—	interpolation	open-cybersec/app.js public/open-cybersec/app.js public/open-llm/app.js
API_BASE	No	—	interpolation	open-rf/app.js public/open-networks/app.js public/open-rf/app.js
BACKUP_ROOT	No	—	shell	modules/open-networks/integration/install-module-files.sh
BASE	No	http://127.0.0.1:3000	shell, interpolation	DEPLOY-GODADDY.md OPENCYBERSEC-QUICKSTART.md OPENCYBERSEC.md UPGRADE-v0.14.0.md rocketchat/outgoing-webhook-test.sh scenarios/run_demo_sequence.sh
BASE_PATH	No	—	interpolation, shell	open-rf/app.js public/open-rf/app.js third_party/ontowiki/application/scripts/travis/install-services.sh
BLAZEGRAPH	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
BUILD	No	—	shell	edge/openpnt-linuxptp/SELF-TEST.sh edge/openssa-sensor/install/install-native-uhd.sh edge/openssa-sensor/native/uhd_spectrum_engine/build-simulation.sh edge/openssa-sensor/native/uhd_spectrum_engine/build.sh
BUILDPATH	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
BUILD_DIR	No	\$ENGINE/build	interpolation	edge/openssa-sensor/install/install-native-uhd.sh edge/openssa-sensor/native/uhd_spectrum_engine/build-simulation.sh edge/openssa-sensor/native/uhd_spectrum_engine/build.sh
BUILD_ROOT	No	—	shell	edge/openpnt-linuxptp/install-linuxptp.sh
CATALINA_BASE	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
CATALINA_HOME	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
CFG	No	—	shell	edge/openssa-sensor/install-demo-sensor.sh
CONFIG	No	—	shell	drivers/install_openpnt_agent.sh edge/opencybersec/install.sh edge/openssa-sensor/install/check-sensor.sh edge/openssa-sensor/install/install-sensor.sh openrf/agent/functions/start-5g-ran-b210-50mhz.sh openrf/agent/functions/start-5g-ran-n78-n310.sh
CORE_DIR	No	—	shell	openrf/agent/functions/start-5g-core.sh openrf/agent/functions/status-5g-core.sh
CROSS_COMPILE	No	—	interpolation	third_party/openil_linuxptp/incdefs.sh
CURRENT	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
DATA_DIR	No	path.join(ROOT	interpolation, process.env	OPENCYBERSEC-QUICKSTART.md OPENCYBERSEC.md RELEASE-MANIFEST-v0.14.0.json UPGRADE-v0.14.0.md server.js
DRIVER	No	—	shell	edge/openssa-sensor/install-demo-sensor.sh edge/openssa-sensor/install/check-sensor.sh edge/openssa-sensor/install/install-ubuntu-deps.sh
EF_STORE_ADAPTER	No	—	getenv, shell	third_party/ontowiki/application/classes/0ntoWiki/Test/IntegrationTestBootstrap.php
ENGINE	No	—	shell	edge/openssa-sensor/install/install-native-uhd.sh
ENV_FILE	No	—	shell	edge/opencybersec/install.sh
EOD_TECH_TARGET	No	@eodtech	process.env	server.js
EUID	No	\$(id -u	interpolation, shell	drivers/install_openpnt_agent.sh edge/opencybersec/install.sh edge/opencybersec/uninstall.sh edge/openpnt-linuxptp/install-linuxptp.sh edge/openpnt-linuxptp/uninstall-linuxptp.sh openrf/agent/install.sh
E_UNREACHABLE	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
FG_ROOT	No	—	shell	edge/openlvc/flightgear/opensof-lvc.xml
FOURSTORE	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
FUSEKI	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
GNB	No	—	shell	openrf/agent/functions/start-5g-ran-b210-50mhz.sh openrf/agent/functions/start-5g-ran-n78-n310.sh
HERE	No	—	shell	edge/openpnt-linuxptp/SELF-TEST.sh edge/openpnt-linuxptp/install-linuxptp.sh edge/openssa-sensor/native/uhd_spectrum_engine/build-simulation.sh edge/openssa-sensor/native/uhd_spectrum_engine/build.sh examples/opencybersec/ingest-examples.sh scenarios/run_demo_sequence.sh
HOME	No	/tmp	process.env, shell	lib/openllm/pipeline-engine.js openrf/agent/functions/start-5g-core.sh openrf/agent/functions/status-5g-core.sh third_party/ontowiki/.travis.yml
HOST	No	0.0.0.0	process.env, interpolation	server.js lib/openrf-controller/server.js
INSTALL_DIR	No	—	shell	edge/opencybersec/install.sh
INSTANCE	No	—	shell	edge/openpnt-linuxptp/install-linuxptp.sh
ISQLFILE	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh
JOBS	No	—	shell	edge/openpnt-linuxptp/install-linuxptp.sh
KBUILD_OUTPUT	No	—	interpolation, shell	third_party/openil_linuxptp/incdefs.sh
KNOWLEDGE_NS	No	—	interpolation	server.js

Variable	Secret-like	Observed default	Mechanism	Evidence
LANG	No	C.UTF-8	process.env	lib/openllm/pipeline-engine.js
LAT	No	—	shell	edge/openssa-sensor/install-demo-sensor.sh
LON	No	—	shell	edge/openssa-sensor/install-demo-sensor.sh
MISSION_KNOWLEDGE_NS	No	—	interpolation	server.js
MOUNT_PATH	No	COMPILED_DEPLOYMENT.mountPath	process.env, interpolation	server.js
NATIVE_SOURCE	No	—	shell	edge/openssa-sensor/install/install-sensor.sh edge/openssa-sensor/install/update-existing-sensor.sh
NODE_ID	No	COMPILED_DEPLOYMENT.nodeId	process.env	server.js edge/openssa-sensor/lib/openssa.js lib/openssa.js
NS	No	—	interpolation	lib/openiia.js
OPENAAR_BATCH_SIZE	No	100	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_CLOCK_SOURCE	No	SYSTEM	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_MAX_SPOOL_MB	No	2048	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_NODE_ID	No	socket.gethostname()	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_RECONNECT_S	No	5	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_RECORDER_ID	No	f"EDGE-{socket.gethostname()}"	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_REPORT_INTERVAL_S	No	30	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_RUN_ID	No	—	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_SERVER	No	http://127.0.0.1:3000	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_SIGNING_KEY	Yes	[REDACTED]	process.env	server.js
OPENAAR_SITE	No	FIELD	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_SNAPSHOT_EVERY_EVENTS	No	100	process.env	server.js

Variable	Secret-like	Observed default	Mechanism	Evidence
OPENAAR_SNAPSHOT_INTERVAL_S	No	30	process.env	server.js
OPENAAR_SPOOL_DIR	No	/var/lib/openaar-edge	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_TIME_UNCERTAINTY_NS	No	0	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_TOPICS	No	—	os.getenv	drivers/openaar_edge_recorder.py
OPENAAR_TYPES	No	—	os.getenv	drivers/openaar_edge_recorder.py
OPENAI_API_KEY	Yes	—	process.env	server.js lib/openllm/providers.js
OPENANALYTICS_CONNECTOR_TIMEOUT_MS	No	60000	process.env	server.js
OPENBUS_API_TOKEN	Yes	[REDACTED]	shell, os.getenv, process.env, getenv, interpolation	OPENKNOWLEDGE-OPENTASK.md OPENLVC-DEMO.md OPENLVC-RTI.md demo_simulator.py server.js drivers/openaar_edge_recorder.py
OPENBUS_MAX_HISTORY	No	500	process.env	server.js
OPENCHAT_DEFAULT_TARGET	No	#eod-ops	process.env	server.js
OPENCOP_TRACK_URL	No	https://opencop.c24.ai/iroapp.ai/api/tracks	process.env	server.js
OPENCOP_UI_URL	No	BUILTIN_OPENCOP_UI_URL	process.env	server.js
OPENCYBERSEC_AGENT_TOKEN	Yes	[REDACTED]	shell, process.env, interpolation	OPENCYBERSEC-QUICKSTART.md OPENCYBERSEC.md server.js examples/opencybersec/ingest-examples.sh
OPENCYBERSEC_OPERATOR_TOKEN	Yes	[REDACTED]	shell, process.env, interpolation	OPENCYBERSEC-QUICKSTART.md OPENCYBERSEC.md server.js examples/opencybersec/ingest-examples.sh
OPENCYBERSEC_READ_TOKEN	Yes	—	process.env	server.js
OPENFILES_HEALTH_URL	No	—	process.env	server.js tools/integrate_opens_of_service_entries.py

Variable	Secret-like	Observed default	Mechanism	Evidence
<code>OPENFILES_PUBLIC_URL</code>	No	—	process.env	<code>tools/integrate_opens of_service_entries.py</code>
<code>OPENFILES_SERVICE_URL</code>	No	—	process.env	<code>server.js</code>
<code>OPENIIA_MAX_EVIDENCE_BYTES</code>	No	<code>12000000</code>	process.env	<code>server.js</code>
<code>OPENISAC_HEALTH_URL</code>	No	—	process.env	<code>server.js</code> <code>tools/integrate_opens of_service_entries.py</code>
<code>OPENISAC_PUBLIC_URL</code>	No	<code>https://bss.dev/live/ isac/</code>	process.env	<code>tools/integrate_opens of_service_entries.py</code>
<code>OPENISAC_SERVICE_URL</code>	No	—	process.env	<code>server.js</code>
<code>OPENKNOWLEDGE_EDITOR_TOKEN</code>	Yes	<code>[REDACTED]</code>	process.env	<code>server.js</code>
<code>OPENKNOWLEDGE_GRAPH</code>	No	<code>https://opensof.local /graph/core</code>	process.env	<code>server.js</code>
<code>OPENKNOWLEDGE_MODEL_FILE</code>	No	<code>path.join(DATA</code>	process.env	<code>server.js</code>
<code>OPENKNOWLEDGE_ONTOWIKI_URL</code>	No	—	process.env	<code>server.js</code>
<code>OPENKNOWLEDGE_SPARQL_ENDPOINT</code>	No	—	process.env	<code>server.js</code>
<code>OPENKNOWLEDGE_TIMEOUT_MS</code>	No	<code>8000</code>	process.env	<code>server.js</code>
<code>OPENLLM_AGENT_MAX_OUTPUT_BYTES</code>	No	—	process.env	<code>lib/openllm/agents.js</code>
<code>OPENLLM_AGENT_TIMEOUT_MS</code>	No	—	process.env	<code>lib/openllm/agents.js</code>
<code>OPENLLM_ALLOW_LOCAL_EXECUTION</code>	No	—	process.env	<code>lib/openllm/pipeline- engine.js</code>
<code>OPENLLM_ANTHROPIC_API_KEY</code>	Yes	<code>[REDACTED]</code>	process.env	<code>server.js</code> <code>lib/openllm/providers .js</code>
<code>OPENLLM_ANTHROPIC_URL</code>	No	<code>https://api.anthropic .com/v1').replace(/\// +\$/</code>	process.env	<code>lib/openllm/providers .js</code>
<code>OPENLLM_ANTHROPIC_VERSION</code>	No	<code>2023-06-01</code>	process.env	<code>lib/openllm/providers .js</code>
<code>OPENLLM_CLAUDE_BIN</code>	No	<code>claude</code>	process.env	<code>lib/openllm/agents.js</code>
<code>OPENLLM_CODEX_BIN</code>	No	<code>codex</code>	process.env	<code>lib/openllm/agents.js</code>
<code>OPENLLM_COMMAND_MODE</code>	No	<code>off').toLowerCase(</code>	process.env	<code>lib/openllm/pipeline- engine.js</code>
<code>OPENLLM_FALLBACK_WRITE_MAX_BYTES</code>	No	—	process.env	<code>lib/openllm/pipeline- engine.js</code>

Variable	Secret-like	Observed default	Mechanism	Evidence
OPENLLM_HEALTH_TIMEOUT_MS	No	—	process.env	lib/openllm/providers.js
OPENLLM_MAX_AUDIT	No	—	process.env	lib/openllm.js
OPENLLM_MAX_RUNS	No	—	process.env	lib/openllm/pipeline-engine.js
OPENLLM_MODEL_CACHE_TIMEOUT_MS	No	—	process.env	lib/openllm/providers.js
OPENLLM_OPENAI_API_KEY	Yes	[REDACTED]	process.env	server.js lib/openllm/providers.js
OPENLLM_OPENAI_URL	No	https://api.openai.com/v1').replace(/\/+\$/	process.env	lib/openllm/providers.js
OPENLLM_OPENBUS_SCHEMA	No	opensof.openbus.event/1.0	process.env	lib/openllm.js
OPENLLM_OPENWEBUI_API_KEY	Yes	[REDACTED]	process.env	server.js lib/openllm/providers.js
OPENLLM_OPENWEBUI_CHAT_PATH	No	/api/chat/completions	process.env	lib/openllm/providers.js
OPENLLM_OPENWEBUI_HEALTH_PATH	No	/health	process.env	lib/openllm/providers.js
OPENLLM_OPENWEBUI_MODELS_PATH	No	/api/models	process.env	lib/openllm/providers.js
OPENLLM_OPENWEBUI_URL	No	process.env.OPENWEBUI_URL	process.env	server.js lib/openllm/providers.js
OPENLLM_OPERATOR_TOKEN	Yes	[REDACTED]	process.env	server.js lib/openllm.js
OPENLLM_PROVIDER_TIMEOUT_MS	No	—	process.env	lib/openllm/providers.js
OPENLLM_QWEN_BIN	No	qwen	process.env	lib/openllm/agents.js
OPENLLM_SANDBOX_CPUS	No	2	process.env	lib/openllm/pipeline-engine.js
OPENLLM_SANDBOX_IMAGE	No	openc5isr-openllm-sandbox:0.1.0	process.env	lib/openllm/pipeline-engine.js
OPENLLM_SANDBOX_MEMORY	No	2g	process.env	lib/openllm/pipeline-engine.js
OPENLLM_SANDBOX_PIDS	No	256	process.env	lib/openllm/pipeline-engine.js
OPENLLM_WORKSPACES_DIRECTORY	No	path.join(ROOT	process.env	server.js
OPENLVC_FEDERATE	No	—	interpolation	edge/openlvc/systemd/openlvc-rti-gateway.service

Variable	Secret-like	Observed default	Mechanism	Evidence
OPENLVC_FEDERATION	No	—	interpolation	edge/openlvc/systemd/openlvc-rti-gateway.service
OPENLVC_HEALTH_URL	No	—	process.env	server.js tools/integrate_opens_of_service_entries.py
OPENLVC_PUBLIC_URL	No	—	process.env	tools/integrate_opens_of_service_entries.py
OPENLVC_RTI_SIDE CAR COMMAND	No	—	interpolation	edge/openlvc/systemd/openlvc-rti-gateway.service
OPENLVC_SERVICE_URL	No	—	process.env	server.js
OPENMAIL_HEALTH_URL	No	—	process.env	server.js tools/integrate_opens_of_service_entries.py
OPENMAIL_PUBLIC_URL	No	—	process.env	tools/integrate_opens_of_service_entries.py
OPENMAIL_SERVICE_URL	No	—	process.env	server.js
OPENNWORKS_AGENT_SOCKET	No	/run/opennetworks/agent.sock	process.env	lib/opennetworks/agent-client.js modules/opennetworks/integration/native-server-example.js
OPENNWORKS_AGENT_TIMEOUT_MS	No	120000	process.env	lib/opennetworks/agent-client.js modules/opennetworks/integration/native-server-example.js
OPENNWORKS_BODY_LIMIT_BYTES	No	2 * 1024 * 1024	process.env	lib/opennetworks/index.js
OPENNWORKS_DATA_DIR	No	path.join(this.rootDir)	process.env	lib/opennetworks/service.js modules/opennetworks/integration/native-server-example.js
OPENNWORKS_EXECUTION_MODE	No	simulate	process.env	lib/opennetworks/service.js modules/opennetworks/integration/native-server-example.js
OPENPNT_AGENT_TOKEN	Yes	[REDACTED]	os.getenv, process.env	drivers/openpnt_agent.py lib/openpnt.js

Variable	Secret-like	Observed default	Mechanism	Evidence
OPENPNT_BUILD_JOBS	No	<code>\$(getconf _NPROCESSORS_ONLN 2>/dev/null echo 2)</code>	interpolation	<code>edge/openpnt- linuxptp/install- linuxptp.sh</code>
OPENPNT_CLOCK_STALE_A FTER_S	No	—	process.env	<code>lib/openpnt- timing.js</code>
OPENPNT_LINUXPTP_BIN DIR	No	—	os.getenv	<code>drivers/openpnt_agent .py drivers/openpnt_linux ptp.py</code>
OPENPNT_NODE_ID	No	—	os.getenv	<code>drivers/openpnt_agent .py drivers/openpnt_linux ptp.py</code>
OPENPNT_POLL_SECONDS	No	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENPNT_POSITION_MAX_ AGE_S	No	—	process.env	<code>lib/openpnt.js</code>
OPENPNT_PTP_CONFIG	No	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENPNT_PTP_INSTANCE	No	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENPNT_PTP_INTERFACE	No	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENPNT_SERVER	No	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENPNT_SPOOL_FILE	No	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENPNT_TAI_UTC_OFFSE T_S	No	—	process.env	<code>lib/openpnt.js</code>
OPENPNT_TDOA_MAX_UNCE RTAINTY_NS	No	—	process.env	<code>lib/openpnt- timing.js</code>
OPENPNT_TDOA_MIN_SENS ORS	No	—	process.env	<code>lib/openpnt- timing.js</code>
OPENPNT_TOKEN	Yes	—	os.getenv	<code>drivers/openpnt_agent .py</code>
OPENRF_5G_CORE_DIR	No	<code>\$HOME/5g/magic-core</code>	interpolation	<code>openrf/agent/function s/start-5g-core.sh openrf/agent/function s/status-5g-core.sh</code>
OPENRF_AGENT_OFFLINE_ SECONDS	No	<code>70</code>	process.env	<code>lib/openrf- controller/server.js</code>
OPENRF_AGENT_TOKEN	Yes	<code>[REDACTED]</code>	process.env, shell	<code>server.js lib/openrf- controller/server.js openrf/API.md</code>
OPENRF_BASE_PATH	No	<code>/open-rf</code>	process.env	<code>lib/openrf- controller/server.js</code>

Variable	Secret-like	Observed default	Mechanism	Evidence
OPENRF_DATA_DIR	No	path.join(DATA	process.env	server.js lib/openrf- controller/server.js
OPENRF_DISPATCH_LEASE_SECONDS	No	90	process.env	lib/openrf- controller/server.js
OPENRF_OPERATOR_TOKEN	Yes	[REDACTED]	process.env, shell	server.js lib/openrf- controller/server.js openrf/API.md openrf/README- UPSTREAM-v0.3.0.md
OPENRF_PYTHON	No	/usr/bin/python3	os.getenv	openrf/agent/src/open rf_agent/util.py
OPENRF_RADIO_ADDRESS	No	192.168.20.2	interpolation	openrf/agent/function s/probe-n310.sh
OPENRF_RADIO_ID	No	N310-01	interpolation	openrf/agent/function s/start-5g-ran-n78- n310.sh
OPENRF_READ_TOKEN	Yes	—	process.env, shell	server.js lib/openrf- controller/server.js openrf/API.md
OPENSOF_BASE	No	http://127.0.0.1:3000	os.getenv	scenarios/run_openeye s_demo.py
OPENSOF_EVENT_URL	No	http://127.0.0.1:3000 /api/event	os.getenv	demo_simulator.py
OPENSOF_ROOT	No	https://wallacecorpte ch.com/live/opensof	interpolation	examples/opencybersec /ingest-examples.sh
OPENSOF_URL	No	http://127.0.0.1:3000	shell, os.getenv, getenv, interpolation	OPENLVC-DEMO.md edge/openlvc/README.m d edge/openlvc/dis_udp_ bridge.py edge/openlvc/rti_open bus_gateway.py edge/openlvc/systemd/ openlvc-ais- bridge.service edge/openlvc/systemd/ openlvc-dis- bridge.service
OPENSSA_ACTIVE_TIMEOUT_S	No	900	process.env	server.js edge/openssa- sensor/SERVER_INTEGRA TION.md edge/openssa- sensor/lib/openssa.js lib/openssa.js

Variable	Secret-like	Observed default	Mechanism	Evidence
OPENSsa_EMITTER_HISTORY_LIMIT	No	2000	process.env	edge/openssa-sensor/lib/openssa.js lib/openssa.js
OPENSsa_EMITTER_SIGHTING_LIMIT	No	500	process.env	edge/openssa-sensor/lib/openssa.js lib/openssa.js
OPENSsa_GEOLOCATION_HISTORY_LIMIT	No	100	process.env	edge/openssa-sensor/lib/openssa.js lib/openssa.js
OPENSsa_ITU_REGION	No	2	process.env	server.js edge/openssa-sensor/SERVER_INTEGRATION.md edge/openssa-sensor/lib/openssa.js lib/openssa.js
OPENSsa_LOCATION_PROFILE	No	—	os.getenv	edge/openssa-sensor/drivers/ssa_sensor.py
OPENSsa_SENSOR_TOKEN	Yes	[REDACTED]	process.env, os.getenv	server.js edge/openssa-sensor/SERVER_INTEGRATION.md edge/openssa-sensor/local_server.js edge/openssa-sensor/demo/run_streaming_demo.py edge/openssa-sensor/lib/openssa.js lib/openssa.js
OPENSsa_UHD_SPECTRUM_ENGINE	No	—	os.getenv	edge/openssa-sensor/drivers/ssa_sensor.py
OPENWEBUI_API_KEY	Yes	[REDACTED]	process.env	server.js lib/openllm/providers.js
OPENWEBUI_CHAT_PATH	No	/api/chat/completions	process.env	server.js
OPENWEBUI_DEFAULT_MODEL	No	—	process.env	server.js
OPENWEBUI_HEALTH_PATH	No	/health	process.env	server.js
OPENWEBUI_MODELS_PATH	No	/api/models	process.env	server.js
OPENWEBUI_URL	No	).replace(/\/+\$/)	process.env	server.js
OPEN_EYES_API_BASE	No	—	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_EYES_ASSET_ID	No	ISAC-RASPBOT-01	os.getenv	drivers/raspbot_openeyes_agent.py

Variable	Secret-like	Observed default	Mechanism	Evidence
OPEN_EYES_DEFAULT_ASSET	No	ISAC-RASPBOT-01	process.env	server.js
OPEN_EYES_HTTP_TIMEOUT	No	3	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_EYES_LOG_LEVEL	No	INFO	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_EYES_RECONNECT_DELAY	No	2	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_EYES_STATUS_INTERVAL	No	0.25	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_EYES_VERIFY_TLS	No	true	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_EYES_VIDEO_FPS	No	15	os.getenv	drivers/raspbot_openeyes_agent.py
OPEN_SOF	No	—	shell	OPENKNOWLEDGE-OPENTASK.md
OWHG	No	—	shell	third_party/ontowiki/application/scripts/makeRelease.sh
PATH	No	/usr/sbin:/usr/bin:/sbin:/bin	os.getenv, process.env, shell	edge/opencybersec/opencybersec_agent.py lib/openllm/pipeline-engine.js lib/openllm/util.js tests/openpnt_agent_smoke_test.py tests/openpnt_linuxptp_wrapper_smoke_test.py third_party/ontowiki/application/scripts/travis/install-services.sh
PHPVERSION	No	—	shell	third_party/ontowiki/application/scripts/travis/install-extensions.sh
PHP_	No	—	shell	third_party/ontowiki/application/scripts/travis/install-extensions.sh
PORT	No	3000	process.env, interpolation	server.js edge/openssa-sensor/local_server.js lib/openrf-controller/server.js
PUBLIC_BASE_URL	No	COMPILED_DEPLOYMENT.publicBaseUrl).replace(/\/+\$/	process.env, interpolation	server.js

Variable	Secret-like	Observed default	Mechanism	Evidence
PWD	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh
PYTHONUNBUFFERED	No	1	systemd	openrf/agent/systemd/openrf-agent.service
RASPBOT_BROWSER_WS_URL	No	—	process.env	server.js
RASPBOT_CONTROL_URL	No	—	process.env	server.js
RASPBOT_LOCAL_URL	No	http://127.0.0.1:6001	os.getenv	drivers/raspbot_openeyes_agent.py
RASPBOT_STREAM_URL	No	—	process.env	server.js
RASPBOT_WS_URL	No	—	os.getenv	drivers/raspbot_openeyes_agent.py
RES	No	—	interpolation	lib/openiia.js
RESULTFILE	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh
ROCKETCHAT_AUTH_TOKEN	Yes	[REDACTED]	process.env	server.js
ROCKETCHAT_BOT_USERNAME	No	openc5.bot	process.env	server.js
ROCKETCHAT_EMBED_URL	No	—	process.env	server.js
ROCKETCHAT_INCOMING_WEBHOOK_URL	No	—	process.env	server.js
ROCKETCHAT_OUTGOING_TOKEN	Yes	[REDACTED]	process.env, interpolation	server.js rocketchat/outgoing-webhook-test.sh
ROCKETCHAT_PUBLIC_URL	No	ROCKETCHAT_URL '').replace(/\./+\$/	process.env	server.js
ROCKETCHAT_URL	No	).replace(/\./+\$/	process.env, interpolation	server.js
ROCKETCHAT_USER_ID	No	—	process.env	server.js
ROLE	No	—	shell	edge/openssa-sensor/install-demo-sensor.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
ROOT	No	—	shell	edge/opencybersec/install.sh edge/openpnt-linuxptp/SELF-TEST.sh edge/openpnt-linuxptp/install-linuxptp.sh edge/openssa-sensor/install-demo-sensor.sh edge/openssa-sensor/install/install-native-uhd.sh edge/openssa-sensor/install/install-sensor.sh
RUN_GROUP	No	—	shell	openrf/agent/install.sh
RUN_ID	No	—	shell	OPENCYBERSEC.md
RUN_USER	No	—	shell	openrf/agent/install.sh
SERVICE	No	—	shell	edge/opencybersec/install.sh
SERVICE_GROUP	No	—	shell	edge/openssa-sensor/install/install-sensor.sh edge/openssa-sensor/install/update-existing-sensor.sh
SERVICE_USER	No	—	shell	edge/openssa-sensor/install/install-sensor.sh edge/openssa-sensor/install/update-existing-sensor.sh
SESAME	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
SITE_ID	No	COMPILED_DEPLOYMENT.siteId	process.env	server.js edge/openssa-sensor/lib/openssa.js lib/openssa.js
SOURCE	No	—	shell	edge/openpnt-linuxptp/install-linuxptp.sh
SOURCE_ROOT	No	—	shell	modules/open-networks/integration/install-module-files.sh
SRC	No	—	shell	drivers/install_openpnt_agent.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
SSA_API	No	—	interpolation	edge/openssa-sensor/public/open-ssa/app.js open-ssa/app.js public/open-ssa/app.js
STAMP	No	—	shell	modules/open-networks/integration/install-module-files.sh
STICKER	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh
STICKERBEGIN	No	—	shell	third_party/ontowiki/application/scripts/vad/prepare.sh
SUDO_USER	No	\$USER	interpolation	edge/openssa-sensor/install/install-sensor.sh edge/openssa-sensor/install/update-existing-sensor.sh openrf/agent/install.sh
SUITE_VERSION	No	—	interpolation	server.js tools/integrate_opensof_service_entries.py
TARGET_ROOT	No	—	shell	modules/open-networks/integration/install-module-files.sh
TASK	No	—	shell	rocketchat/outgoing-webhook-test.sh
TOKEN	Yes	—	shell	edge/openssa-sensor/install-demo-sensor.sh rocketchat/outgoing-webhook-test.sh
TOMCAT_VERSION	No	—	shell	third_party/ontowiki/application/scripts/travis/install-services.sh
TRACK_API	No	—	interpolation	integrations/opencop-openeyes/patched-static/map.js
TRAVIS_PHP_VERSION	No	—	shell	third_party/ontowiki/application/scripts/travis/install-extensions.sh third_party/ontowiki/application/scripts/travis/install-services.sh

Variable	Secret-like	Observed default	Mechanism	Evidence
<code>UHD_INCLUDE_DIRS</code>	No	—	interpolation	<code>edge/openssa-sensor/native/uhd_spectrum_engine/CMakeLists.txt</code>
<code>UHD_LIBRARIES</code>	No	—	interpolation	<code>edge/openssa-sensor/native/uhd_spectrum_engine/CMakeLists.txt</code>
<code>USER</code>	No	—	shell	<code>edge/openssa-sensor/SENSOR_INSTALL.md</code> <code>edge/openssa-sensor/install-demo-sensor.sh</code> <code>edge/openssa-sensor/install/install-sensor.sh</code> <code>edge/openssa-sensor/install/update-existing-sensor.sh</code> <code>openrf/README-UPSTREAM-v0.3.0.md</code> <code>third_party/ontowiki/application/scripts/travis/install-services.sh</code>
<code>VIRTTMP</code>	No	—	shell	<code>third_party/ontowiki/application/scripts/vad/prepare.sh</code>
<code>VIRTUOSO</code>	No	—	shell	<code>third_party/ontowiki/application/scripts/travis/install-services.sh</code>
<code>VIRTUOSO_T</code>	No	—	shell	<code>third_party/ontowiki/application/scripts/vad/prepare.sh</code>
<code>WORK</code>	No	—	shell	<code>edge/openssa-sensor/install-demo-sensor.sh</code>

Configuration policy

- Store edition-specific configuration outside the immutable release directory.
- Do not store passwords, tokens, private keys or complete credentials in BookStack, source control, command history or URLs.
- Document variable purpose, valid values, default behavior, reload/restart requirement and owning service.
- Use separate secrets per distribution/instance and rotate them through a recorded procedure.

- Validate required variables before service start and fail clearly instead of silently selecting unsafe defaults.
-

Maintainer Notes

Add human-reviewed deployment notes, corrections, decisions, screenshots, and links here. Content outside the generated block is preserved on future runs.

systemd Services

systemd Services

Field	Value
Distribution	WCT English — OpenC5ISR
Product	OpenC5ISR
Release	0.15.1
Deployment	openc5isr-en.wallacecorptech.com
Source	/srv/wct/releases/OpenC5ISR-v0.15.0
Evidence	Release and readable host service definitions
Source fingerprint	63d2b1097707e25d666401cdc6362e395968600a40a08690210cd8c0b75fbf50
Status	Generated baseline — human review required

“ **Verification boundary:** This page combines platform design guidance with static evidence from the release. It does not prove that every detected interface is enabled, reachable, secure, or operational in the deployed environment.

Observed service units

Unit	Description	User	Working directory	ExecStart	Restart	Evidence
opencybersec-agent.service	OpenCyberSec Defensive Edge Sensor Agent	opencybersec	—	/opt/opencybersec-agent/opencybersec_agent.py --config /etc/opencybersec-agent.json	on-failure	edge/opencybersec/systemd/opencybersec-agent.service

Unit	Description	User	Working directory	ExecStart	Restart	Evidence
openlvc-ais-bridge.service	OpenLVC AIS NMEA Bridge	rocketman	/opt/opensof/edge/openlvc	/usr/bin/python3 /opt/opensof/edge/openlvc/ais_nmea_bridge.py --opensof \${OPENSOF_URL} --token [REDACTED] --bind 0.0.0.0 --port 10110	on-failure	edge/openlvc/systemd/openlvc-ais-bridge.service
openlvc-dis-bridge.service	OpenLVC IEEE DIS UDP Bridge	rocketman	/opt/opensof/edge/openlvc	/usr/bin/python3 /opt/opensof/edge/openlvc/dis_udp_bridge.py --opensof \${OPENSOF_URL} --token [REDACTED] --bind 0.0.0.0 --port 3000	on-failure	edge/openlvc/systemd/openlvc-dis-bridge.service
openlvc-flightgear-bridge.service	OpenLVC FlightGear UDP Bridge	rocketman	/opt/opensof/edge/openlvc	/usr/bin/python3 /opt/opensof/edge/openlvc/flightgear_bridge.py --opensof \${OPENSOF_URL} --token [REDACTED] --bind 0.0.0.0 --port 5505	on-failure	edge/openlvc/systemd/openlvc-flightgear-bridge.service
openlvc-rti-gateway.service	OpenLVC OpenBus to HLA RTI Gateway	rocketman	/opt/opensof/edge/openlvc	/usr/bin/python3 /opt/opensof/edge/openlvc/rti_openbus_gateway.py --opensof \${OPENSOF_URL} --token [REDACTED] --federation \${OPENLVC_FEDERATION} --federate \${OPENLVC_FEDERATION} --sidecar-command \${OPENLVC_RTI_SIDE CAR_COMMAND}	on-failure	edge/openlvc/systemd/openlvc-rti-gateway.service

Unit	Description	User	Working directory	ExecStart	Restart	Evidence
openpnt-phc2sys@.service	OpenPNT linuxptp phc2sys instance %i	root	–	/opt/openpnt/bin/openpnt-linuxptp run phc2sys --instance /etc/openpnt/linuxptp/instances/%i.json --bin-dir /opt/openpnt/linuxptp/bin	on-failure	edge/openpnt-linuxptp/systemd/openpnt-phc2sys@.service
openpnt-tp4l@.service	OpenPNT linuxptp tp4l instance %i	root	–	/opt/openpnt/bin/openpnt-linuxptp run tp4l --instance /etc/openpnt/linuxptp/instances/%i.json --bin-dir /opt/openpnt/linuxptp/bin	on-failure	edge/openpnt-linuxptp/systemd/openpnt-tp4l@.service
openpnt-ts2phc@.service	OpenPNT linuxptp ts2phc instance %i	root	–	/opt/openpnt/bin/openpnt-linuxptp run ts2phc --instance /etc/openpnt/linuxptp/instances/%i.json --bin-dir /opt/openpnt/linuxptp/bin	on-failure	edge/openpnt-linuxptp/systemd/openpnt-ts2phc@.service
openrf-agent.service	OpenRF Radio Agent	OPENRF_USER	/opt/openrf-agent	/usr/local/bin/openrf-agent --config /etc/openrf/openrf-agent.json	always	openrf/agent/systemd/openrf-agent.service
openc5isr-wct-en.service	OpenC5ISR WCT English Node.js Server	wct-ops	/srv/wct/instances/openc5isr-en/current	/usr/local/bin/npm start	on-failure	/etc/systemd/system/openc5isr-wct-en.service

Authoritative deployment checklist

- Copy unit files to /etc/systemd/system only from a reviewed release/deployment source.
- Run systemctl daemon-reload after unit changes, then enable/start the intended instance.
- Use a dedicated non-login service account with read-only release access and only required persistent-state permissions.
- Set WorkingDirectory and absolute ExecStart paths; do not depend on an interactive shell profile.

- Add health-aware dependencies and restart limits so a bad backend does not create a restart storm.

Verification commands

```
systemctl cat <unit>.service
systemctl status <unit>.service --no-pager
systemctl show <unit>.service -p User -p Group -p WorkingDirectory -p ExecStart
journalctl -u <unit>.service -n 200 --no-pager
```

Maintainer Notes

Add human-reviewed deployment notes, corrections, decisions, screenshots, and links here. Content outside the generated block is preserved on future runs.

Nginx Configuration

Nginx Configuration

Field	Value
Distribution	WCT English — OpenC5ISR
Product	OpenC5ISR
Release	0.15.1
Deployment	openc5isr-en.wallacecorptech.com
Source	/srv/wct/releases/OpenC5ISR-v0.15.0
Evidence	Release and readable host Nginx configuration
Source fingerprint	63d2b1097707e25d666401cdc6362e395968600a40a08690210cd8c0b75fbf50
Status	Generated baseline — human review required

“ **Verification boundary:** This page combines platform design guidance with static evidence from the release. It does not prove that every detected interface is enabled, reachable, secure, or operational in the deployed environment.

Observed proxy configuration

Evidence	server_name	listen	location	proxy_pass
/etc/nginx/sites-available/openc5isr-en.wallacecorptech.com	openc5isr-en.wallacecorptech.com openc5isr-en.wallacecorptech.com	443 ssl [::]:443 ssl ipv6only=on 80 [::]:80	/	http://127.0.0.1:3101/

Proxy requirements

- Terminate TLS with a valid certificate and redirect clear-text HTTP to HTTPS.
- Preserve Host, X-Real-IP, X-Forwarded-For and X-Forwarded-Proto headers.
- Configure WebSocket upgrade headers on real-time routes.
- Set upload/body/time limits deliberately for imagery, video, files and long-running analytics.
- Keep each distribution hostname mapped to its intended service/port; test routing after every release.
- Run `nginx -t` before reload and retain the last-known-good configuration.

Verification commands

```
sudo nginx -t  
sudo systemctl reload nginx  
curl -I https://openc5isr-en.wallacecorp.tech/
```

Maintainer Notes

Add human-reviewed deployment notes, corrections, decisions, screenshots, and links here. Content outside the generated block is preserved on future runs.

Ports and Network Bindings

Ports and Network Bindings

Field	Value
Distribution	WCT English — OpenC5ISR
Product	OpenC5ISR
Release	0.15.1
Deployment	openc5isr-en.wallacecorptech.com
Source	/srv/wct/releases/OpenC5ISR-v0.15.0
Evidence	Static numeric port extraction
Source fingerprint	63d2b1097707e25d666401cdc6362e395968600a40a08690210cd8c0b75fbf50
Status	Generated baseline — human review required

“ **Verification boundary:** This page combines platform design guidance with static evidence from the release. It does not prove that every detected interface is enabled, reachable, secure, or operational in the deployed environment.

Observed port candidates

Port	Protocol	Evidence	Source
1	tcp	port mapping to 30	public/open-lvc/index.html
1	tcp	port mapping to 80	third_party/openil_linuxptp/config.c
1	tcp	port mapping to 80	third_party/openil_linuxptp/configs/G.8275.1.cfg
1	tcp	port mapping to 80	third_party/openil_linuxptp/configs/automotive-master.cfg

Port	Protocol	Evidence	Source
1	tcp	port mapping to 80	third_party/openil_linuxptp/configs/automotive-slave.cfg
1	tcp	port mapping to 80	third_party/openil_linuxptp/configs/default.cfg
1	tcp	port mapping to 80	third_party/openil_linuxptp/configs/gPTP.cfg
2	tcp	port mapping to 00	tests/openpnt_agent_smoke_test.py
10	tcp	port mapping to 150	third_party/ontowiki/extensions/datagathering/scripts/jquery.autocomplete.js
11	tcp	port mapping to 43	third_party/ontowiki/extensions/themes/silverblue/scripts/libraries/jquery.dimensions.js
11	tcp	port mapping to 20	third_party/ontowiki/extensions/translations/ru/core.csv
12	tcp	port mapping to 00	third_party/ontowiki/extensions/exconf/Archive.php
13	tcp	port mapping to 15	third_party/ontowiki/application/config/SysBase.rdf
13	tcp	port mapping to 59	third_party/ontowiki/application/scripts/vad/ow_vad_sticker_template.xml
13	tcp	port mapping to 29	third_party/ontowiki/extensions/themes/silverblue/scripts/libraries/jquery.simplemodal.js
18	tcp	port mapping to 30	third_party/ontowiki/extensions/datagathering/scripts/jquery.autocomplete.js
19	tcp	port mapping to 29	third_party/ontowiki/extensions/exconf/resources/exconf.css
19	tcp	port mapping to 08	third_party/ontowiki/extensions/filter/resources/jquery.treeview.js
20	tcp	command argument	UPGRADE-v0.11.0.md
21	tcp	port mapping to 01	third_party/ontowiki/extensions/exconf/pclzip.lib.php
21	tcp	port mapping to 39	third_party/ontowiki/extensions/exconf/resources/togglebutton.css
30	tcp	port mapping to 10	edge/openssa-sensor/lib/openssa.js
30	tcp	port mapping to 10	lib/openssa.js

Port	Protocol	Evidence	Source
80	tcp	port mapping to 443	third_party/ontowiki/extensions/themes/silverblue/scripts/libraries/jquery-1.9.1.js
200	tcp	port mapping to 404	edge/openssa-sensor/lib/openssa.js
200	tcp	port mapping to 422	lib/open-networks/service.js
200	tcp	port mapping to 404	lib/openllm.js
200	tcp	port mapping to 404	lib/openssa.js
200	tcp	port mapping to 404	third_party/ontowiki/extensions/themes/silverblue/scripts/libraries/jquery-1.9.1.js
201	tcp	port mapping to 200	lib/openrf-controller/server.js
319	tcp	command argument	third_party/openil_linuxptp/udp.c
319	tcp	command argument	third_party/openil_linuxptp/udp6.c
320	tcp	command argument	third_party/openil_linuxptp/udp.c
320	tcp	command argument	third_party/openil_linuxptp/udp6.c
401	tcp	port mapping to 400	lib/openrf-controller/server.js
413	tcp	port mapping to 400	lib/open-networks/index.js
443	tcp	port mapping to 80	server.js
1000	tcp	port mapping to 20	public/open-networks/app.js
1000	tcp	port mapping to 200	third_party/ontowiki/extensions/themes/silverblue/scripts/libraries/jquery-ui-1.8.22.js
3000	tcp	URL	OPENCYBERSEC-QUICKSTART.md
3000	tcp	URL	OPENLVC-RTI.md
3000	tcp	URL	README-OPENEYES.md
3000	tcp	URL	SCENARIOS.md
3000	tcp	URL	demo_simulator.py
3000	tcp	URL	drivers/eod_technician_agent.py
3000	tcp	URL	drivers/n310_sensor_agent.py

Port	Protocol	Evidence	Source
3000	tcp	URL	drivers/openaar_edge_recorder.py
3000	tcp	URL	drivers/openanalytics-agent.env.example
3000	tcp	URL	drivers/raspbot_task_agent.py
3000	tcp	URL	drivers/sse_to_udp_task_bridge.py
3000	tcp	command argument	edge/openlvc/README.md
3000	tcp	URL	edge/openlvc/ais_nmea_bridge.py
3000	tcp	URL	edge/openlvc/dis_udp_bridge.py
3000	tcp	URL	edge/openlvc/flightgear_bridge.py
3000	tcp	URL	edge/openlvc/rti_openbus_gateway.py
3000	tcp	command argument	edge/openlvc/systemd/openlvc-dis-bridge.service
3000	tcp	URL	edge/openssa-sensor/QUICKSTART-B210.md
3000	tcp	URL	edge/openssa-sensor/README.md
3000	tcp	URL	edge/openssa-sensor/config/ssa-sensor-simulation.json
3000	tcp	URL	edge/openssa-sensor/config/ssa-sensor-uhd-b210-local.json
3000	tcp	URL	edge/openssa-sensor/demo/run_streaming_demo.py
3000	tcp	URL	lib/openllm/providers.js
3000	tcp	URL	open-daa/open-analytics/app.js
3000	tcp	URL	rocketchat/outgoing-webhook-test.sh
3000	tcp	URL	scenarios/run_demo_sequence.sh
3000	tcp	URL	scenarios/run_eod_floor_mission.py
3000	tcp	URL	scenarios/run_follow_mission.py
3000	tcp	URL	scenarios/run_fusion_demo.py

Port	Protocol	Evidence	Source
3000	tcp	URL	scenarios/run_openeyes_demo.py
3000	tcp	URL	scenarios/send_eod_message.py
3000	tcp	URL	server.js
3030	tcp	command argument	third_party/ontowiki/application/scripts/travis/README.md
3600	tcp	configuration directive	server.js
5505	tcp	command argument	OPENLVC-DEMO.md
5505	tcp	command argument	edge/openlvc/README.md
5505	tcp	command argument	edge/openlvc/systemd/openlvc-flightgear-bridge.service
6001	tcp	URL	README-OPENEYES.md
6001	tcp	command argument	drivers/README-RASPBOT-OPENEYES.txt
6001	tcp	URL	drivers/openpnt_raspbot_guidance.py
6001	tcp	URL	drivers/raspbot-openeyes.env.example
6001	tcp	URL	drivers/raspbot_openeyes_agent.py
7101	tcp	command argument	SCENARIOS.md
8075	tcp	command argument	openrf/README-UPSTREAM-v0.3.0.md
8075	tcp	URL	openrf/agent/config/openrf-agent.json
8080	tcp	URL	third_party/ontowiki/application/scripts/travis/README.md
8080	tcp	URL	third_party/ontowiki/application/scripts/travis/install-services.sh
8088	tcp	URL	third_party/ontowiki/application/scripts/travis/README.md
8095	tcp	URL	openrf/API.md
8800	tcp	URL	drivers/mock_rocketchat.py
8888	tcp	URL	drivers/openanalytics-agent.json.example
8888	tcp	URL	open-daa/open-analytics/app.js

Port	Protocol	Evidence	Source
8888	tcp	URL	<code>public/open-daa/open-analytics/app.js</code>
8890	tcp	URL	<code>third_party/ontowiki/application/scripts/travis/README.md</code>
8890	tcp	URL	<code>third_party/ontowiki/application/scripts/vad/vad.ini</code>
9000	tcp	URL	<code>open-lvc/app.js</code>
9999	tcp	URL	<code>third_party/ontowiki/application/scripts/travis/install-services.sh</code>
10110	tcp	command argument	<code>edge/openlvc/README.md</code>
10110	tcp	command argument	<code>edge/openlvc/systemd/openlvc-ais-bridge.service</code>
18782	tcp	URL	<code>tests/compiled_deployment_smake_test.py</code>

Port governance

A numeric occurrence is only a candidate. Confirm the owning process with `ss -ltnup`, the service with `systemctl`, the container mapping with `docker compose ps`, and the public route with Nginx. Document whether each port binds to loopback, a management interface, an operational network or all interfaces.

Maintainer Notes

Add human-reviewed deployment notes, corrections, decisions, screenshots, and links here. Content outside the generated block is preserved on future runs.